

The ParaComm Cable Head or Rope socket is used to attach the Slick-E-Line® to the downhole tool string (for logging or mechanical services). The Cable head is connected to the ParaComm Communication Head (PCH).



The assembly consists of a robust body with external fishing neck, insulated sleeve design which maintains form and ensures continuous communication and a brass wedge (pear drop).

The pear drop is grooved to accommodate the Slick-E-Line® and comes complete with a securing grub screw. The more pull applied on the Slick-E-Line®, the more the pear drop pulls into the sleeve giving a tighter grip on the Slick-E-Line®.

The standard fishing head allows for quick and easy fishing operations.

Features:

- Provide connection of the Slick-E-Line® to the tool string.
- Robust body design
- Standard fishing neck

| Part Number: | A1200406 | |
|----------------|----------|----------|
| Diameter | 43 mm | 1 11/16" |
| Fish Neck | 30.2 mm | 1.19" |
| Make up length | 297 mm | 11.7" |
| Weight | 2.3 kg | 5 lb. |

| | | |
|-----------------------|----------------------------------|------------|
| Temperature rating | 177°C | 350°F |
| Pressure rating | 103.4 MPa | 15,000 psi |
| Tensile strength | > 200 kN | 45 klb |
| Lower head connection | 1 3/16" -12 TPI, inverted GO Box | |
| Materials | Corrosion resistant throughout | |