

This Slick-E-Line® Central Junction Box Ex is the explosion proof central box of the ParaComm communication of the Slick-E-Line® system. The Junction Box is used to provide both power and communication to the ParaComm DP panel, ParaComm Antenna and ParaSheave.

The Central Junction box is fitted inside a winch unit with connectors to fit the cabled assemblies to components of the Slick-E-Line® system. This box is designed for use in a Zone 1 explosion hazardous area (option: RigSafe).

The power cable can be either hard wired or connected via an explosion proof connector the available power source.



| | | |
|---------------------|--------------------|--------|
| Part Number: | A1205319 | |
| Temperature rating | -20 / + 40°C | |
| Dimensions (WxHxD) | 357 x 270 x 182 mm | |
| Weight | 12 kg | 26 lb. |

| | |
|-----------------------|--|
| Electric supply | 230VAC (optionally 12 or 24 VDC) |
| Electrical connection | EX PoE with connectors to: Antenna DP panel External Ethernet |
| Power Cable | 5 m leads only or with connector |
| Bottom connection | Wedged mounting block (lockable) |
| EX Classification | CE Ex II 2G IIB T3 (zone 1) |
| Option | A1206730 Non-explosion proof |
| Standards | EN-IEC 60079-0 EN-IEC 60079-1 EN-IEC 60079-14 |