

With this cross over sub, the Sondex Production Logging Tools can be mechanically as well as electrically connected below the Slick-E-Line® toolstring. The Cross over can be placed directly below any Paradigm PPU. The data from the PLT tools is sent to surface via the ParaComm system. The Sondex PLT data will be visualized in ParaLog and ParaOffice. The PLT will also be stored in the memory of the PPU for back up post job processing.



Available Sondex PLT tools

1	CTF	Capacitance & Temperature & Flowmeter
2	PGR	Production Gamma Ray Tool
3	QPC	Quartz Pressure / CCL Combination tool
4	FDR	Fluid Density Radioactive
5	ILS	In-line Spinner Flowmeter
6	PDC	Production Dual Caliper
7	QPS	Quartz Pressure, Single sensor tool
8	PRT	Platinum Resistance Thermometer tool
9	CCL	Casing Collar Locator
10	CWH	Capacitance Water Hold Up tool
11	CFBE/CFJE	Spinner Flowmeter Electronics
12	RBT	Radial Bond Tool
13	MIT	Multi-Finger Imaging Tool
14	FDI	Fluid Density Inertial
15	NTO	Noise tool

Part Number:

A1213291

Diameter	43 mm	1 11/16"
Overall length	420,4 mm	16.55"
Make up length	385,4 mm	15.17"
Weight	2,0 kg	4.4 lb.

Temperature rating	177°C	350°F
Pressure rating	103.4 MPa	15,000 psi
Upper head connection	1.475" – 10 TPI – Stub Acme Box	
Bottom head connection	1 3/16" -12 UN	
Materials	Corrosion resistant throughout	